

ANNOTATED SHEET SHOWING CHANGES




Fig. 1A





1/38




Fig. 1A




Fig. 1B



3/38




Fig. 1C



First Named Inventor: Frankie F. Roohparvar
SYNCHRONOUS FLASH MEMORY WITH ACCESSIBLE PAGE DURING WRITE
Atty Docket No. 400.044US01 Serial No. 09/627,770

4/38




Fig. 2A

Fig. 2B

Fig. 2




Fig. 2A




Fig. 2B



7/38




Fig. 3



8/38




Fig. 4




Fig. 5



10/38




Fig. 6





Fig. 7




12/38



NOTE: Each READ command may be to either bank. DQM is LOW.

 DON'T CARE

Fig. 8



NOTE: A CAS latency of three is used for illustration. The READ command may be to any bank, and the WRITE command may be to any bank. If a CAS latency of one is used, then DQM is not required.

 DON'T CARE

Fig. 9



14/38




Fig. 10



15/38





Fig. 11



NOTE: A CAS latency of two is used for illustration. The WRITE command may be to any bank and the READ command may be to any bank. DQM is LOW. A READ to the bank undergoing the WRITE ISM operation may output invalid data.

 DON'T CARE

Fig. 12




Fig. 13





Fig. 14




ADDRESS RANGE

	Bank	Row	Column		
Bank 3	3	FFF	FFH	256K-Word Block	15
	3	C00	00H		
	3	BFF	FFH	256K-Word Block	14
	3	800	00H		
	3	7FF	FFH	256K-Word Block	13
	3	400	00H		
	3	3FF	FFH	256K-Word Block	12
	3	000	00H		
Bank 2	2	FFF	FFH	256K-Word Block	11
	2	C00	00H		
	2	BFF	FFH	256K-Word Block	10
	2	800	00H		
	2	7FF	FFH	256K-Word Block	9
	2	400	00H		
	2	3FF	FFH	256K-Word Block	8
	2	000	00H		
Bank 1	1	FFF	FFH	256K-Word Block	7
	1	C00	00H		
	1	BFF	FFH	256K-Word Block	6
	1	800	00H		
	1	7FF	FFH	256K-Word Block	5
	1	400	00H		
	1	3FF	FFH	256K-Word Block	4
	1	000	00H		
Bank 0	0	FFF	FFH	256K-Word Block	3
	0	C00	00H		
	0	BFF	FFH	256K-Word Block	2
	0	800	00H		
	0	7FF	FFH	256K-Word Block	1
	0	400	00H		
	0	3FF	FFH	256K-Word Block	0
	0	000	00H		

Word-wide (x16)

 Software Lock = Hardware-Lock Sectors
 RP# = V_{HH} to unprotect if either the
 block protect or device protect bit is set.

 Software Lock = Hardware-Lock Sectors
 RP# = V_{CC} to unprotect but must be V_{HH}
 if the device protect bit is set.

See BLOCK PROTECT/UNPROTECT SEQUENCE for
 detailed information.

Fig. 15



20/38




Fig. 16



21/38




Fig. 17



22/38




Fig. 18




Fig. 19



24/38




Fig. 20




Fig. 21



26/38




Fig. 22



27/38




Fig. 23




Fig. 26




Fig. 27



32/38




Fig. 28




Fig. 29



34/38




Fig. 30




Fig. 31



36/38





Fig. 32



37/38



400

Fig. 33




Fig. 34